
CIRCUIT INTEGRITY CABLES

FR-SIR-F 90 / Signal- and communication cables

BETAflam® Fire alarm cables, 300/500 V, circuit integrity acc. to BS 6387 or IEC 60331, LSOH



Application

Shielded fire alarm cable 300/500 V for fixed installation in cable systems with the highest fire performance and circuit integrity requirements. For high temperature conditions and extra long expected lifetime.
Typical applications:
- Fire alarm circuits
- Fire detection circuits
- Emergency signal/control circuits
- Voice alarm systems
- Emergency lighting system etc.

Especially recommended in areas where human and animal life as well as valuable property are exposed to high risk in case of fire.

Construction

Conductor	Bare annealed soild copper, acc. to VDE 0295 / IEC 60228, class 1 or 2
Insulation	BETAflam® SIR silicone rubber, cross-linked
Core colour	See below
Shield	Aluminium laminated foil with tinned drain wire
Shared inner covering	Halogenfree tape
Sheath	BETAflam® mineral copolymer
Sheath colour	Red

Advantages

- High safety standard: BS 6387 C.W.Z, fully tested and certified by LPCB
- High safety standard
- Fire tested by Electrosuisse
- Low Smoke Zero Halogen (LSOH)
- RoHS and REACH compliant
- Operating temperature 90 °C
- High LOI
- Space saving installation due to small outer diameter
- Very long lifetime
- Made in Switzerland

0000069 V02 © Studer Cables AG / Technical modifications reserved

Electrical properties

Rated value	U_0 / U	300 / 500 V AC
Test voltage	Core/core	2.0 kV, 50 Hz / 5 min.

Thermal properties

Max. operating temperature	fixed installation	+90°C
Min. ambient temperature	fixed installation	-30°C
Max. ambient temperature	during laying	+70°C
Min. ambient temperature	during laying	-5°C
Max. short circuit temperature		+250°C (max. 5s)

Mechanical properties

Bending radius	during laying	≥ 8 x Ø
Bending radius	fixed installation	≥ 6 x Ø

Material properties / Standards

Halogen free	IEC 60754-1; BS EN 60754-1
No corrosive gases	IEC 60754-2, BS EN 60754-2

Material properties / Standards

No Toxicity of gases	Def Stan 02-713
Minimal smoke density	IEC 61034-1 & -2; BS EN 61034-1 & -2
Flame retardant	IEC 60332-1-2
No flame spread on bunched cables	IEC 60332-3-22, -24 (Cat. A & C); BS EN 60332-3-22, -24 (Cat. A & C)
Circuit integrity	IEC 60331-11, -21
Circuit integrity	BS 6387 C.W.Z.

Approvals

LPCB - BRE Group
www.redbooklive.com

Additional information

Laying conditions:

	Also for electrical installations outside of cable ducts.
	Not recommended for permanently high humid ambient.
	Shield from direct sunlight.

0000069 V02© Studer Cables AG / Technical modifications reserved

Construction Cross-sec. [n x mm2]	Color code	Conductor class	Core-Ø [mm]	Outer-Ø [mm]	Weight [kg/km]	Fire load [kWh/m]	Part no.
2 × 1*	sw,ws	2	1.3	7.2	69	0.181	312861
2 × 1.5	bl,br	1	1.4	8.3	98	0.227	305208
2 × 1.5	sw,ws	1	1.4	8.3	98	0.227	306010
2 × 1.5	rt,sw	1	1.4	8.3	98	0.227	307892
2 × 2.5	bl,br	1	1.74	9.4	136	0.280	305210
2 × 2.5	sw,ws	1	1.74	9.4	136	0.280	306009

* Not C.W.Z., but according to IEC 60331-11 and -21

0000069 V02© Studer Cables AG / Technical modifications reserved